

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR LETTERS PATENT

**METHODS AND APPARATUS TO CONTROL TRANSMISSION OF A  
MULTICARRIER WIRELESS COMMUNICATION CHANNEL THROUGH  
MULTIPLE ANTENNAS**

Inventor(s):  
Sumeet Sandhu

Prepared by: Michael A. Proksch,  
Sr. Patent Counsel

**intel.**®

Intel Corporation  
2111 N.E. 25th Avenue  
Hillsboro, OR 97124-5961  
Phone: (503) 264.3059  
Facsimile: (503) 264.1729

**Express Mail Label: EV325527737US**

3  
5  
7  
9  
11  
13  
15  
17  
19  
21  
23  
25  
27  
29  
31  
33  
35  
37  
39  
41  
43  
45  
47  
49  
51  
53  
55  
57  
59  
61  
63  
65  
67  
69  
71  
73  
75  
77  
79  
81  
83  
85  
87  
89  
91  
93  
95  
97  
99  
101  
103  
105  
107  
109  
111  
113  
115  
117  
119  
121  
123  
125  
127  
129  
131  
133  
135  
137  
139  
141  
143  
145  
147  
149  
151  
153  
155  
157  
159  
161  
163  
165  
167  
169  
171  
173  
175  
177  
179  
181  
183  
185  
187  
189  
191  
193  
195  
197  
199  
201  
203  
205  
207  
209  
211  
213  
215  
217  
219  
221  
223  
225  
227  
229  
231  
233  
235  
237  
239  
241  
243  
245  
247  
249  
251  
253  
255  
257  
259  
261  
263  
265  
267  
269  
271  
273  
275  
277  
279  
281  
283  
285  
287  
289  
291  
293  
295  
297  
299  
301  
303  
305  
307  
309  
311  
313  
315  
317  
319  
321  
323  
325  
327  
329  
331  
333  
335  
337  
339  
341  
343  
345  
347  
349  
351  
353  
355  
357  
359  
361  
363  
365  
367  
369  
371  
373  
375  
377  
379  
381  
383  
385  
387  
389  
391  
393  
395  
397  
399  
401  
403  
405  
407  
409  
411  
413  
415  
417  
419  
421  
423  
425  
427  
429  
431  
433  
435  
437  
439  
441  
443  
445  
447  
449  
451  
453  
455  
457  
459  
461  
463  
465  
467  
469  
471  
473  
475  
477  
479  
481  
483  
485  
487  
489  
491  
493  
495  
497  
499  
501  
503  
505  
507  
509  
511  
513  
515  
517  
519  
521  
523  
525  
527  
529  
531  
533  
535  
537  
539  
541  
543  
545  
547  
549  
551  
553  
555  
557  
559  
561  
563  
565  
567  
569  
571  
573  
575  
577  
579  
581  
583  
585  
587  
589  
591  
593  
595  
597  
599  
601  
603  
605  
607  
609  
611  
613  
615  
617  
619  
621  
623  
625  
627  
629  
631  
633  
635  
637  
639  
641  
643  
645  
647  
649  
651  
653  
655  
657  
659  
661  
663  
665  
667  
669  
671  
673  
675  
677  
679  
681  
683  
685  
687  
689  
691  
693  
695  
697  
699  
701  
703  
705  
707  
709  
711  
713  
715  
717  
719  
721  
723  
725  
727  
729  
731  
733  
735  
737  
739  
741  
743  
745  
747  
749  
751  
753  
755  
757  
759  
761  
763  
765  
767  
769  
771  
773  
775  
777  
779  
781  
783  
785  
787  
789  
791  
793  
795  
797  
799  
801  
803  
805  
807  
809  
811  
813  
815  
817  
819  
821  
823  
825  
827  
829  
831  
833  
835  
837  
839  
841  
843  
845  
847  
849  
851  
853  
855  
857  
859  
861  
863  
865  
867  
869  
871  
873  
875  
877  
879  
881  
883  
885  
887  
889  
891  
893  
895  
897  
899  
901  
903  
905  
907  
909  
911  
913  
915  
917  
919  
921  
923  
925  
927  
929  
931  
933  
935  
937  
939  
941  
943  
945  
947  
949  
951  
953  
955  
957  
959  
961  
963  
965  
967  
969  
971  
973  
975  
977  
979  
981  
983  
985  
987  
989  
991  
993  
995  
997  
999

**METHODS AND APPARATUS TO CONTROL TRANSMISSION OF A MULTICARRIER WIRELESS COMMUNICATION CHANNEL THROUGH MULTIPLE ANTENNAS**

**RELATED APPLICATIONS**

[0001] This application claims priority to provisional application number 60/TBD filed on TBD by Shao, et al., entitled *An Apparatus and Associated Methods to Implement a High-Throughput Wireless Communication System*, the disclosure of which is expressly incorporated herein for all purposes.

**TECHNICAL FIELD**

[0002] Embodiments of the present invention are generally directed to a wireless communication system and, more particularly, to methods and apparatus to control transmission of a multicarrier wireless communication channel through multiple antenna(e).

**BACKGROUND**

[0003] A multicarrier communication system such as, e.g., Orthogonal Frequency Division Multiplexing (OFDM), Discrete Multi-tone (DMT) and the like, is typically characterized by a frequency band associated with a communication channel being divided into a number of smaller sub-bands (*subcarriers* herein). Communication of information (e.g., data, audio, video, etc.) between stations in a multicarrier communication system is performed by dividing the informational content into multiple pieces (e.g., symbols), and then transmitting the pieces in parallel via a number of the separate subcarriers. When the symbol period transmitted through a subcarrier is longer than a maximum multipath delay in the channel, the effect of intersymbol interference may be significantly reduced.

4 [0004] While multicarrier communication systems hold the promise of high throughput  
communication channels, technical challenges persist. For example, in certain applications such  
as, for example a wireless local area network (WLAN) deep fades can occur in the channel that  
may persist over a significant period of time. Further, due to environmental conditions (e.g.,  
5 home office, business, etc.), the wireless channels may typically encounter significant dispersion  
due to multipath propagation that limits the maximum achievable rates.

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

10 [0005] Embodiments of the present invention are illustrated by way of example, and not by way  
of limitation, in the figures of the accompanying drawings in which like reference numerals refer  
to similar elements and in which:

**Fig. 1** is a block diagram of an example multicarrier wireless network incorporating the  
teachings of the present invention, according to one example implementation;

15 **Fig. 2** is a block diagram of an example transceiver incorporating the teachings of the  
present invention, according to one example implementation;

**Fig. 3** is a flow chart of an example method for mapping information to one or more  
antenna(e) and subcarrier(s), according to one embodiment of the invention;

**Fig. 4** is a flow chart of an example method for mapping information to one or more  
antenna(e) and subcarrier(s), according to one embodiment of the invention;

20 **Figs. 5 and 6** provide graphical illustrations of transmit diversity and space-frequency  
interleaving for two transmit antennas, in accordance with embodiments of the present invention;

**Fig. 7** is a graphical illustration of the improvement to one or more channel  
characteristics through use of an embodiment of the invention;

Fig. 8 provides a graphical illustration of the improvement to one or more channel characteristics through use of an embodiment of the invention; and

Fig. 9 is a block diagram of an example article of manufacture including content which, when executed by an accessing machine, causes the machine to implement one or more aspects of embodiment(s) of the invention.

### **DETAILED DESCRIPTION**

[0006] Embodiments of an apparatus and associated methods to control transmission of a multicarrier wireless communication channel are generally introduced herein. In this regard, aspects of the present invention may well be used to implement any of a number of wireless communication platforms such as, e.g., wireless local area network (WLAN), wireless personal area network (WPAN), wireless metro-area networks (WMAN), cellular networks, and the like.

[0007] With this disclosure, an innovative approach to improving the resilience of the multicarrier communication channel is disclosed, wherein an advanced OFDM processing technique is added to a multiple input, multiple output (MIMO) transceiver that utilizes more than one transmit/receive chain at each end of the wireless link. Those skilled in the art will appreciate, in view of the following discussion, that the disclosed combination of MIMO and OFDM (MIMO-OFDM ) appears particularly promising for high-throughput wireless LAN application.

[0008] According to a first aspect of the invention, a transmit diversity capability is introduced, which provides a near-optimal method for mapping uncoded content (e.g., quadrature amplitude modulation (QAM) symbols) received from a host device, or an application/agent executing thereon, to multiple antennas and OFDM tones. While the transmit diversity architecture

introduced herein provides full-order diversity, it may only provide a limited code rate per OFDM slot.

[0009] According to another aspect of the invention, the transmit diversity architecture is extended to provide a higher code rate by means of space-frequency interleaving (SFI). As developed more fully below, SFI provides a near-optimal technique for mapping coded information (e.g., bits, frames, symbols, etc.) onto multiple antennas and OFDM tones.

[0010] Reference throughout this specification to “one embodiment” or “an embodiment” means that a particular feature, structure or characteristic described in connection with the embodiment is included in at least one embodiment of the present invention. Thus, appearances of the phrases “in one embodiment” or “in an embodiment” in various places throughout this specification are not necessarily all referring to the same embodiment. Furthermore, the particular features, structures or characteristics may be combined in any suitable manner in one or more embodiments.

### **Example Network Environment**

[0011] **Fig. 1** illustrates a block diagram of a wireless communication environment within which the teachings of the present invention may be practiced. As shown, network 100 depicts two devices 102, 104, each comprising one or more wireless transmitter(s) and receiver(s) (cumulatively, a transceiver) 108, 116, baseband and media access control (MAC) processing capability 112, 114, and memory 110, 118, each coupled as shown. As used herein, the devices 102, 104 communicate information between one another via a multicarrier wireless communication channel 106, established between the transceiver(s) 108, 116 through one or

more antenna(e) associated with the devices. According to one embodiment, one of the devices 102 may be coupled to another network 120.

[0012] According to one aspect of the invention, an innovative diversity agent is introduced within the device(s) introduce and manage one or more elements of diversity within the

5 multicarrier wireless channel. On the transmit side of a communication channel, the diversity agent may selectively map content (e.g., received from a host device, application, agent, etc.) to one or more antenna(e) and/or OFDM tones to generate a MIMO-OFDM transmit signal. In support of the receive side of the communication channel, the diversity agent may selectively demap the content received via the MIMO-OFDM wireless channel (e.g., 106) from multiple  
10 antennas and OFDM tones. While not specifically denoted in Fig. 1, the diversity agent may well be implemented in one or more of the baseband and MAC processing element(s) (112, 114) and/or the transceiver element(s) (108, 116), although the invention is not so limited.

[0013] According to one example embodiment, the diversity agent may selectively process content received from the host device (e.g., 102, 104) to implement full-order transmit diversity,  
15 although the invention is not limited in this respect. As developed below, diversity agent may map uncoded content (e.g., quadrature amplitude modulated (QAM) symbols) received from the host device (102, 106) or applications executing thereon, onto multiple antennas and OFDM tones to effect spatial diversity in the transmit link of channel (106).

[0014] According to one embodiment, the diversity agent may selectively process content  
20 received from the host device (e.g., 102, 104) to introduce space-frequency interleaving (SFI) of the content onto multiple antennas and OFDM tones. In this regard, as developed below, diversity agent may selectively map coded information (e.g., bits, bytes, blocks, symbols, frames, packets, etc.) received from the host device or applications executing thereon, onto multiple

antennas and OFDM tones by performing one or more of antenna multiplexing, 802.11a interleaving, QAM mapping, and cyclic tone shifting, although the invention is not limited in this regard.

[0015] In addition to the foregoing, the diversity agent may selectively implement an innovative technique(s) for decoding information from a received OFDM channel processed as above. In this regard, an innovative receive diversity agent is introduced to demap and/or deinterleave content received from a channel 106 generated in accordance with one or both of the encoding techniques introduced above. According to one embodiment, receive diversity agent receives content as decoded modulation information (e.g., bits) and generates de-mapped and/or de-interleaved content, respectively.

[0016] But for the introduction of the diversity agent introduced above, devices 102, 104 are intended to represent any of a wide range of electronic devices with wireless communication capability including, for example, a laptop, palmtop or desktop computer, a cellular telephone (e.g., a 2G, 2.5G, 3G or 4G handset), a personal digital assistant, an WLAN access point (AP), a WLAN station (STA), and the like.

[0017] As used herein, baseband and MAC processing element(s) 112, 114 may be implemented in one or more processors (e.g., a baseband processor and an application processor), although the invention is not limited in this regard. As shown, the processor element(s) 112, 114 may couple to memory 110, 118, respectively, which may include volatile memory such as DRAM, non-volatile memory such as Flash memory, or alternatively may include other types of storage such as a hard disk drive, although the scope of the invention is not limited in this respect. Some portion or all of memory 110, 118 may well be disposed within the same package as the processor element(s) 112, 114, or may be disposed on an integrated circuit or some other

medium external to element(s) 112, 114. According to one embodiment, baseband and MAC processing element(s) 112, 114 may implement at least a subset of the features of diversity agent described below, and/or may provide control over a diversity agent implemented within an associated transceiver (108, 116), although the invention is not limited in this regard.

5 [0018] Similarly, but for the introduction of the diversity agent to effect the MIMO-OFDM channelization developed more fully below, transceivers 108, 116 are also intended to reflect any of a variety of multicarrier wireless communication transceivers known in the art. In this regard, a transmitter element of the transceivers receive content from a host device, process the received content to generate an OFDM transmit signal, and then transmits that OFDM signal over a link  
10 (e.g., forward link) to a remote device via one or more antennae. A receiver element of the receivers receives multiple instances of the forward link via one or more antenna(e), and selectively processes the received signal(s) to extract a representation of the originally encoded content. Again, the introduction of the diversity agent enables the wireless transceiver within the device(s) to implement the MIMO-OFDM features described below. According to one  
15 embodiment, each of the transmitters and receivers may well include one or more processing chains.

[0019] As used herein, network 120 is intended to represent any of a broad range of communication networks including, for example a plain-old telephone system (POTS) communication network, a local area network (LAN), metropolitan area network (MAN), wide-  
20 area network (WAN), global area network (Internet), cellular network, and the like. According to one example implementation, device 102 represents an access point (AP), while device 104 represents a station (STA), each of which suitable for use within an IEEE 802.11n wireless local



area network (WLAN), and each utilizing the innovative space-frequency interleaving and transmit diversity techniques introduced above, and developed more fully below.

### **Example Transceiver Architecture**

5 [0020] Fig. 2 illustrates a block diagram of an example transmitter architecture and an example receiver architecture according to one example embodiment of the invention. To illustrate these architectures within the context of a communication channel between two devices, a transmitter from one device (e.g., 102) and a receiver from another device (e.g., 104) associated with a communication link are depicted. Those skilled in the art will appreciate that a transceiver in  
10 either device (102, 104) may well comprise a transmitter architecture and a receiver architecture as detailed in Fig. 2, although the scope of the invention is not limited in this regard. It should be appreciated that transmitter and receiver architectures of greater or lesser complexity that nonetheless implement the innovative transmit diversity and/or space-frequency interleaving described herein are anticipated by the scope and spirit of the claimed invention.

15 [0021] According to one example embodiment, a transmitter architecture 200 is depicted comprising one or more of a serial to parallel transform 210, a (transmit) diversity agent 212, one or more inverse discrete Fourier transform (IDFT) element(s) 214, a cyclic prefix, or guard interval, insertion element 216 coupled with one or more antenna(e) 220A...M through an associated one or more radio frequency (RF) elements 218, although the invention is not limited  
20 in this regard. According to one embodiment, transmitter architecture 200 may be implemented within transceiver 108 and/or 116. Although depicted as a number of separate functional elements, those skilled in the art will appreciate that one or more elements of transmitter architecture 200 may well be combined into a multi-functional element, and conversely

functional elements may be split into multiple functional elements without deviating from the invention.

[0022] As used herein, serial-to-parallel (S/P) transform 210 receives information (e.g., bits, bytes, frames, symbols, etc.) from a host device (or, an application executing thereon, e.g., email, audio, video, etc.) for processing and subsequent transmission via the communication channel.

According to one embodiment, the received information is in the form of quadrature amplitude modulated (QAM) symbols (i.e., wherein each symbol represents two bits,  $b_i$  and  $b_j$ ). According to one embodiment, serial-to-parallel transform 210 takes the information and generates a number of parallel substreams of the information, which are passed to one or instances of diversity agent 212. Although depicted as a separate functional element, serial to parallel transform 210 may well be included within the diversity agent 212, or other element of the transmitter 200.

[0023] According to one embodiment, diversity agent 212 selectively introduces an element of transmit diversity into the information streams received from the S/P transform 210. In particular, according to one example embodiment, the informational content is selectively mapped to one or more antenna(e) and OFDM tones. According to one example implementation, if content received from the host device at diversity agent 212 is not in the form of QAM symbols, diversity agent may perform pre-coding to map the received information to QAM symbols, although the invention is not limited in this regard. Indeed, diversity agent may well introduce transmit diversity to any linear combination of input symbols.

[0024] In any case, diversity agent 212 takes the input (e.g., QAM symbols) and repetitively disperses them (bits, symbols, etc.) across  $M_t$  transmit antennas, and a number ( $N$ ) of OFDM tones for each of a plurality of Rayleigh fading channel taps ( $L$ ), although the invention is not

limited in this regard. By selectively dispersing the content in this manner, full order diversity (Mt Mr L, where Mr is the number of receive antennae) may be achieved. An example method for introducing transmit diversity is presented below with reference to Fig. 3, and a graphical illustration of symbols processed in accordance with an example transmit diversity mechanism is provided in Fig. 5.

[0025] In accordance with another aspect of the invention, diversity agent 212 may well include the resources to implement a space-frequency interleaving (SFI) mechanism. In this regard, diversity agent 212 may well include one or more of an antenna multiplexing element, a tone interleaving element, a QAM interleaving element, a QAM mapping element and a cyclic tone shifting element, although the invention is not limited in this regard. According to one embodiment, diversity agent 212 may treat adjacent coded bits as one symbol, and spreads this information across space and frequency, e.g., using the transmit diversity repetition scheme introduced above. According to one embodiment, the content received from S/P transform 210 is first interleaved across at least a subset of transmit antenna(e) Mt, and then across a number of OFDM tones for each of a plurality of the Rayleigh fading channel taps (L), although the invention is not limited in this regard. Indeed, these functional elements need not necessarily be applied in the order described above. Moreover, the amount of cyclic tone shift may well be modified to any value between zero (0) and the number data tones (Nds), and there may be a cyclic shift across antennas instead of, or in addition to the shift across tones. An example method for implementing the space-frequency interleaving is developed more fully below, with reference to Fig. 4, and a graphical representation of SFI is presented with reference to Fig. 6.

[0026] In either case, content from the transmit diversity agent 212 is passed to one or more inverse discrete Fourier transform (IDFT) element(s) 214. According to one embodiment, an

inverse fast Fourier transform (IFFT) element(s), although the invention is not limited in this regard. According to one embodiment, the number of IDFT elements 214 is commensurate with the number of transmit antenna(e), i.e., transmit radio frequency (RF) chains. In this regard, IDFT element(s) 214 may receive a plurality (Z) of encoded substreams from the diversity agent  
5 212, and converts the content from a frequency domain representation to a time domain representation of the content, although the invention is not limited in this regard.

[0027] The time domain content from the IDFT element(s) 214 is passed to CPI element(s) 216. According to one embodiment, CPI 216 may introduce a cyclical prefix, or a guard interval in the signal, before it is passed to a radio frequency (RF) front-end 218 for amplification, filtering  
10 and subsequent transmission via an associated one or more antenna(e) 220A...M.

[0028] To extract content processed by a transmitter architecture 200, above, an example receiver architecture 250 is introduced. As shown, an RF front-end 254 receives a plurality of signals impinging on one or more receive antennae 240A...N. For ease of explanation and description going forward, in accordance with one example embodiment, the number (N) of  
15 receive antenna(e) is equal to Mr. According to one embodiment, each receive antenna has a dedicated receive chain, where the number of receive front-end elements 254, CPR elements 256 and FFT elements are commensurate with the number (N) of receive antenna(e) (e.g., Mr).

[0029] The RF front end 254 may pass at least a subset of the received signal(s) to a cyclic prefix removal element(s) 256, although the invention is not limited in this regard. According to one  
20 embodiment, CPR 256 removes any cyclic prefix or guard interval that may have been introduced during transmit processing of the received signal(s).

[0030] The content from CPR 256 is then provided to an associated one or more of fast Fourier transform (FFT) element(s) 258. According to one embodiment, FFT elements 258 transform

the received signals from an associated receive chain from the time domain to the frequency domain, for subsequent demultiplexing and decoding of a representation of the content embedded within the received transmission. Thus, a plurality of frequency domain representations of the received signal(s) are presented to receive diversity agent 260.

5 [0031] According to one aspect of the present invention, receive diversity agent 260 may perform a complementary function to that performed by transmit diversity agent 212. In this regard, receive diversity agent 260 may perform the complement to the transmit diversity and/or space frequency interleaving introduced above. In the case of transmit diversity, receive diversity agent 260 may demap the QAM symbols, prior to QAM demodulation and parallel to  
10 serial conversion 262 to extract a representation (I') of the content encoded within the received signal(s). In the case of SFI, receive diversity agent 260 performs deinterleaving and decoding, before providing the output content to the parallel to serial converter 262 which generates the representation (I') of the content encoded within the received signal(s). According to one embodiment, diversity agent 260 may well implement a minimum mean square error (MMSE)  
15 spatial demapper followed by soft Viterbi decoding, although the invention is not limited in this regard.

[0032] Although depicted as a number of functional blocks, those skilled in the art will appreciate that one or more of the foregoing elements may well be implemented in hardware, software, firmware, or any combination thereof. Moreover, although not explicitly denoted, it  
20 will be appreciated by those skilled in the art that one or more elements such as, e.g., diversity agent 212, 260 may well receive control input from baseband and/or MAC processing elements (e.g., 112, 114). According to one embodiment, diversity agents 212, 260 may well implement one or more of transmit diversity and space-frequency interleaving, and communicate which

MIMO-OFDM scheme is being used through an exchange of channel state information. In this regard, diversity agent 212, 260 and the transmit diversity/SFI techniques associated therewith, may be adapted according to observed channel delay spread and transmit or receive antenna correlation information (i.e., channel state information).

5

#### **EXAMPLE DIVERSITY AGENT OPERATION**

[0033] Having briefly introduced an example network environment and diversity agent architecture, above, a discussion of each of the MIMO-OFDM techniques introduced herein will now be developed more fully with reference to Figs. 3-7. For ease of description and  
10 understanding, the development of these techniques will be presented in flow-chart form with continued reference, where appropriate, to example elements in Figs. 1 and 2, although the invention is not limited in this regard.

[0034] Turning to **Fig. 3**, a flow chart of an example method 300 for implementing transmit diversity is disclosed, according to one example embodiment. As shown, the method begins  
15 with block 302, wherein the diversity agent 212 receives content for processing. According to one example embodiment, the received content is a plurality of substreams of information received from a serial to parallel transform, although the invention is not limited in this regard. According to one embodiment, the received content is in the form of complex symbols that are linear or nonlinear combinations of input QAM symbols. According to one embodiment,  
20 diversity agent 212 may receive the content from a QAM modulator, wherein the received content is in the form of QAM symbols, although the invention is not limited in this regard. According to another embodiment, diversity agent 212 receives uncoded information stream(s) of bits, and converts the content into QAM symbols.

[0035] In block 304, diversity agent 212 cyclically distributes the QAM symbols across one or more antennae and one or more OFDM tones. According to one embodiment, diversity agent 212 captures spatial diversity through the development of  $M \times N/L$  blocks of QAM symbols (where  $N$  is the number of OFDM tones, and  $L$  is the number of Rayleigh fading channel taps), where the symbols applied to each antenna are offset by a cyclical shift. By repeating these frequency blocks  $L$  times across the number of OFDM tones, diversity agent 212 introduces an element of frequency diversity into the channel as well.

[0036] According to one example embodiment, the number of frequency blocks may be adaptively modified according to multipath conditions in the channel. In this regard, a larger delay spread among frequency blocks may be employed by diversity agent 212 when there is high delay spread ( $L$ ), and fewer blocks may be used for lower delay spread. Moreover, when there is a risk of horizontal wraparound of symbols, wherein the same symbol is transmitted on the same tone, or a very close tone, on a different antenna, diversity agent 212 may well increase or decrease the dispersion to remove this wraparound condition, as appropriate. A graphical illustration of the transmit diversity blocks are presented with reference to Fig. 5.

[0037] In block 306, the blocks generated by diversity agent 212 are provided to the remainder of the transmit processing chain (e.g., IFFT 214, et seq.) to enable the transmitter to complete channel processing on the distributed content for transmission via the one or more antenna(e) and OFDM tones.

[0038] Turning to **Fig. 4**, a flow chart of an example method 400 for implementing space-frequency interleaving (SFI) is introduced, according to one embodiment of the invention. As shown, the technique begins in block 402, where diversity agent 212 receives encoded content. As above, the encoded content may be received, e.g., from forward error correcting (FEC)

encoder, a convolutional encoder, a Reed Solomon encoder, and LDPC encoder, a trellis encoder, a turbo coder a BCH coder, etc., which may be an element of diversity agent 212, although the invention is not limited in this regard. According to one implementation, diversity agent 212 may assume a sliding window memory such as that provided by a convolutional encoder, although the invention is not limited in this respect. Indeed, for other codes, diversity agent 212 may rearrange/interleave the input so as to be correlated in a sliding window fashion. In general, the output codeword from any code may be treated as a QAM symbol  $x_1$ , per the transmit diversity aspect described above, and constituent codeword bits may then be spread using the space-frequency interleaving techniques described herein.

[0039] Diversity agent 212 may then perform antenna multiplexing on the received encoded information. According to one embodiment, adjacent bits of the received content are first mapped to the  $M_t$  antennas. For example, assume the total number of bits= $M_t \cdot N_{CBPS}$ , where  $N_{CBPS}$  is the number of coded and punctured bits mapped to forty-eight (48) tones of an OFDM symbol (as used, e.g., in accordance with the IEEE Std. 802.11a (1999) specification, the disclosure of which is expressly incorporated herein by reference for all purposes), although the invention is not limited in this regard. The bits indexed by  $m:M_t:M_t \cdot N_{CBPS}$  are mapped to the  $m^{th}$  antenna.

[0040] In block 404, diversity agent 212 may interleave the resulting groups of  $N_{CBPS}$  bits on each antenna. According to one embodiment, diversity agent 212 may implement this interleaving in accordance with the 802.11a interleaver, which consists of two elements: tone interleaving, and QAM interleaving (see, e.g., IEEE Std. 802.11a-1999, Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) specifications, incorporated herein for all purposes).



[0041] According to one example embodiment, diversity agent 212 may ensure that adjacent coded bits are mapped onto nonadjacent subcarriers to perform the tone interleaving. According to one embodiment, the interleaver depth determines how many tones separate adjacent coded bits. In general, this separation should be equal to the coherence bandwidth of the channel, e.g.,  $N/L$  (where  $N$ =DFT size, and  $L$ =the length of the channel response in time), although the invention is not limited in this respect. In this regard, the interleaver depth is proportional to the length of the channel impulse in time ( $L$ ).

[0042] As used herein, according to one embodiment, interleaver depth may be defined as the separation between bits on adjacent tones in each frequency block. For example, if there are 1:48 input bits to be mapped to 48 tones with a depth of 16 (i.e., per 802.11a interleaver), where the bits are mapped to tones 1:48 column-by-column, bits 1, 17, 33 and 2 are mapped to tones 1, 2, 3 and 4, respectively. More particularly, the mapping would look like:

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32
33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48

If we change the depth to 12, we get the following mapping, where bits 1, 13, 25, 37 and 2 are mapped to tones 1, 2, 3, 4 and 5 respectively:

1	2	3	4	5	6	7	8	9	10	11	12
13	14	15	16	17	18	19	20	21	22	23	24
25	26	27	28	29	30	31	32	33	34	35	36
37	38	39	40	41	42	43	44	45	46	47	48

[0043] According to one example embodiment, diversity agent 212 may adapt the interleaver depth to the observed value of  $L$ . Depending on perceived multipath conditions, a high  $L$  will result in a large interleaver depth, and vice versa. According to one embodiment, diversity agent 212 may set the interleaver depth based on a worst case channel response condition, e.g., where

L=worst case delay spread=length of the cyclic prefix of an OFDM symbol (e.g., 16 in an 802.11a compliant system).

[0044] Thus, for arbitrary values of N (e.g., 96 or 108 when multiple 802.11a channels are bonded together to provide high throughput), a key design criterion that determines performance contemplated by the diversity agent 212 is the separation of adjacent coded bits as a function of the channel's coherence bandwidth. If the channel bandwidth increases as in channel bonding without affecting inter-tone spacing, the coherence bandwidth will not change (over the same set of multipath channels). If a larger DFT size is taken within the same channel bandwidth, diversity agent 212 may change the tone spacing such that adjacent coded bits are separated accordingly by a proportionally larger number of tones.

[0045] To perform QAM interleaving, diversity agent 212 may ensure that adjacent coded bits are mapped alternately onto less and more significant bits of the constellation and, as such, long runs of low reliability (LSB) bits are avoided. According to one example embodiment, diversity agent 212 performs the tone and QAM interleaving in accordance with the following mathematical descriptions, respectively:

$$i=(N_{CBPS}/16)(k \bmod 16)+\text{floor}(k/16) \quad [1]$$

where  $k=0,1,\dots,N_{CBPS}-1$ ; and the function floor denotes the largest integer not exceeding the parameter.

$$j=s \times \text{floor}(i/s) + (i + N_{CBPS} - \text{floor}(16 \times i/N_{CBPS})) \bmod s \quad [2]$$

where the value of s is determined by the number of coded bits per subcarrier,  $N_{BPSC}$ , according to  $s=\max(N_{BPSC}/2,1)$ . According to one embodiment, a diversity agent 260 in a receiver may employ a deinterleaver which performs the inverse relation defined by the above two permutations, although the invention is not limited in this regard.

[0046] In block 406, diversity agent 212 may map the interleaved content to QAM symbols.

According to one embodiment, diversity agent 212 may include a bit-to-QAM mapper, wherein

multiple bits are mapped to the QAM symbols. According to one example embodiment, the

OFDM subcarriers are modulated using BPSK, QPSK, 16-QAM, 64-QAM, 128-QAM or 256-

QAM, depending on the coding rate to be employed, but the scope of the invention is not limited

in this regard. According to one embodiment, the encoded and interleaved binary serial input

data may be divided into groups of  $N_{\text{BPSC}}$  (e.g., 1, 2, 4 or 6) bits and converted into complex

numbers representing QAM constellation points. The conversion may be performed according

to Gray coded constellation mappings, although the invention is not limited in this respect.

[0047] In block 408, diversity agent 212 introduces a cyclic shift to the resultant QAM symbols

on each antenna with respect to the other antenna(e). According to one embodiment, as

introduced above, diversity agent 212 shifts the symbols destined for the  $m^{\text{th}}$  antenna by  $m-1$

tones vis-à-vis the 1<sup>st</sup> antenna. As used herein, the cyclic tone shift introduced by diversity agent

may well be greater than 1. Indeed, according to one embodiment, the cyclic tone shift

introduced by diversity agent 212 is adaptive based, at least in part, spatial correlation – the more

correlated the fading on different antennas, the greater the tone shift from antenna to antenna. In

certain implementations, e.g., where the number of transmit antennas ( $M_t$ ) is high, diversity

agent may shift by more than one tone from antenna to antenna to avoid wrap around and ensure

good performance.

[0048] In this regard, according to one embodiment, diversity agent 212 may repeat each bit  $M_t$

times, and then perform the SFI technique introduced herein on the larger coded sequence. For

example, if the original coded bit sequence is  $[b_1, b_2, b_3, b_4]$  and there are two transmit antennas

( $M_t=2$ ), diversity agent 212 may expand the received bit sequence to  $[b_1 b_1 b_2 b_2 b_3 b_3 b_4 b_4]$ .

It should be appreciated, from the disclosure herein, that there may be other ways to expand each the coded sequence rather than simple repetition, e.g., by taking into account the resulting multidimensional space-frequency constellations, etc.

[0049] The space-frequency interleaved blocks are then processed for transmission via one or more antenna(e) and OFDM tones, as introduced above. An example graphical illustration of the space-frequency interleaved blocks generated by diversity agent 212 is provided with reference to Fig. 6, below.

[0050] Although not particular detailed, those skilled in the art will appreciate from the discussion above, that a receive diversity agent 260 may implement selectively implement either of the foregoing methods in a complementary (e.g., reverse) order to demap, or deinterleave, respectively, content received on signals processed in accordance with the above transmit diversity or space-frequency interleaving techniques. For example, the deinterleaving technique may comprise one or more of cyclically shifting the tones, QAM to bit mapping, deinterleaving, and antenna demultiplexing, although the invention is not limited in this regard.

[0051] Turning to Fig. 5, a graphical illustration of an example transmit diversity blocks generated in accordance with an embodiment of the invention is presented. In accordance with the example embodiment of Fig. 5, a diversity block of  $M_t \times N/L$  is used. In this case, diversity agent 212 generates an L number  $2 \times N/L$  matrices of QAM symbols. The technique illustrated in Fig. 5 is extensible to cover situations of  $M_t > 2$  by, e.g., incrementing the cyclic delay on each additional transmit antenna according to  $(M_t - 1)$  on successive antennae. It should be appreciated that the space frequency codeword in Fig. 5 is from a Viterbi decoder that decodes across tones while taking into account the repetition of symbols across L blocks, although the invention is not limited in this regard.

[0052] Turning to Fig. 6 a graphical illustration of an example space-frequency interleaving blocks generated in accordance with an embodiment of the invention is illustrated. As above, for ease of illustration and not limitation, the SFI blocks depicted correspond to an embodiment wherein  $M_t=2$ , but is extensible to implementations of  $M_t>2$  in accordance with the techniques described above.

[0053] Fig. 7 presents a graphical illustration evidencing the performance characteristics associated with various mapping techniques (i.e., single input, single output (1x1 SISO), spatial multiplexing (where bits are interleaved across tones, but not antennae), and space-frequency interleaving (SFI)). According to the illustrated embodiment, Fig. 7 graphically illustrates the performance (e.g., measured in bit error rate (BER) and packet error rate (PER) over  $E_s/N_0$ ) for a 54 Mbps/antenna. As shown, the SFI technique exhibits a modest gain of about one decibel (1dB) in signal to noise ratio (SNR) performance relative to conventional (simpler) techniques for a receiver consisting of an MMSE spatial demapper and a soft Viterbi decoder, but should be larger for more sophisticated receivers.

[0054] Although depicted or described as comprising a number of functional elements, those skilled in the art will appreciate, based on the discussion herein, that alternate embodiments of the diversity agent 212 are anticipated within the scope and spirit of the invention. According to one example embodiment, a diversity agent that omits the antenna multiplexing and cyclic tone shift features is anticipated. In accordance with this example embodiment, diversity agent may map blocks of contiguous bits to each of at least a subset of antenna(e), and then perform 802.11a tone and QAM interleaving, and bit-to-QAM mapping described above, although the invention is not limited in this regard. A diversity agent that performs the inverse operations is also anticipated.

[0055] Fig. 8 depicts a graphical illustration of a performance comparison of SFI vs. spatial multiplexing for a lower data rate of 6 Mbps per transmit antenna. As shown, the performance improvement introduced by SFI is more pronounced at lower data rates. Thus, it should be appreciated from the discussion herein that certain advantages of the proposed technique may be even more pronounced in realistic channels with impairments such as antenna gain imbalance, I/Q mismatch etc.

### **Alternate Embodiment(s)**

[0056] Fig. 9 illustrates a block diagram of an example storage medium comprising content which, when invoked, may cause an accessing machine to implement one or more aspects of the diversity agent 212, 260 and/or associated methods 300, 400. In this regard, storage medium 900 includes content 902 (e.g., instructions, data, or any combination thereof) which, when executed, causes an accessing appliance to implement one or more aspects of SMA 212, 260, described above.

[0057] The machine-readable (storage) medium 900 may include, but is not limited to, floppy diskettes, optical disks, CD-ROMs, and magneto-optical disks, ROMs, RAMs, EPROMs, EEPROMs, magnet or optical cards, flash memory, or other type of media / machine-readable medium suitable for storing electronic instructions. Moreover, the present invention may also be downloaded as a computer program product, wherein the program may be transferred from a remote computer to a requesting computer by way of data signals embodied in a carrier wave or other propagation medium via a communication link (e.g., a modem, radio or network connection).

[0058] In the description above, for the purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the present invention. It will be apparent, however, to one skilled in the art that the present invention may be practiced without some of these specific details. In other instances, well-known structures and devices are shown in block diagram form.

[0059] Embodiments of the present invention may be used in a variety of applications. Although the present invention is not limited in this respect, the circuits disclosed herein may be used in microcontrollers, general-purpose microprocessors, Digital Signal Processors (DSPs), Reduced Instruction-Set Computing (RISC), Complex Instruction-Set Computing (CISC), among other electronic components. However, it should be understood that the scope of the present invention is not limited to these examples.

[0060] Embodiments of the present invention may also be included in integrated circuit blocks referred to as core memory, cache memory, or other types of memory that store electronic instructions to be executed by the microprocessor or store data that may be used in arithmetic operations. In general, an embodiment using multistage domino logic in accordance with the claimed subject matter may provide a benefit to microprocessors, and in particular, may be incorporated into an address decoder for a memory device. Note that the embodiments may be integrated into radio systems or hand-held portable devices, especially when devices depend on reduced power consumption. Thus, laptop computers, cellular radiotelephone communication systems, two-way radio communication systems, one-way pagers, two-way pagers, personal communication systems (PCS), personal digital assistants (PDA's), cameras and other products are intended to be included within the scope of the present invention.

[0061] The present invention includes various operations. The operations of the present invention may be performed by hardware components, such as those shown in Figs. 1 and/or 2, or may be embodied in machine-executable content (e.g., instructions) 702, which may be used to cause a general-purpose or special-purpose processor or logic circuits programmed with the instructions to perform the operations. Alternatively, the operations may be performed by a combination of hardware and software. Moreover, although the invention has been described in the context of a computing appliance, those skilled in the art will appreciate that such functionality may well be embodied in any of number of alternate embodiments such as, for example, integrated within a communication appliance (e.g., a cellular telephone).

[0062] Many of the methods are described in their most basic form but operations can be added to or deleted from any of the methods and information can be added or subtracted from any of the described messages without departing from the basic scope of the present invention. Any number of variations of the inventive concept are anticipated within the scope and spirit of the present invention. In this regard, the particular illustrated example embodiments are not provided to limit the invention but merely to illustrate it. Thus, the scope of the present invention is not to be determined by the specific examples provided above but only by the plain language of the following claims.